Fast assembly concealed hinge with integrated Silent System

- **Sensys 8645i**
- **Opening angle 110°, packaging unit 200 ea.**

- Concealed hinge with clip on installation and integrated Silent System
- Quality classification under EN 15570, Level 3
- For door thickness 15 - 24 mm
- Cup diameter 35 mm
- Cup depth 12.8 mm
- Integrated +/- 2 mm overlay adjustment
- Integrated depth adjustment + 3 mm / - 2 mm
- Height adjustment at mounting plate
- Hinge arm material: steel, nickel plated
- Hinge cup material: steel, nickel plated

Sensys 8645i, opening angle 110°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay Base B 12.5 mm	half overlay Base B 3 mm	inset Base B -4 mm	PU
For screwing on TH 52		-	**9 071 205**	**9 071 206**	**9 071 207**	200 ea.
For pressing in TH 53		ø 10 x 11	**9 071 208**	**9 071 209**	**9 071 210**	200 ea.
Fix fast assembly THS 55		ø 10 x 6	**9 071 220**	**9 071 221**	**9 071 222**	200 ea.
For screwing on TB 52		-	**9 071 223**	**9 071 224**	**9 071 225**	200 ea.
For pressing in TB 53		ø 8 x 11	**9 071 226**	**9 071 227**	**9 071 228**	200 ea.
Fix fast assembly TB 55		ø 8 x 6	**9 071 238**	**9 071 239**	**9 071 240**	200 ea.